

LWL
TR-74-15
c. 2



TECHNICAL REPORT NO. 74-15

LOCKING DEVICE FOR VEHICLE RADIOS

By

Robert P. McGowan
Mobility Branch.

April 1974

Final Report

TECHNICAL LIBRARY
BLDG. 305
ABERDEEN PROVING GROUND, MD.
STEAP-TL

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

U. S. ARMY LAND WARFARE LABORATORY

Aberdeen Proving Ground, Maryland 21005

LWL
TR-74-15
c. 2

20081015 075

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

DISPOSITION INSTRUCTIONS

Destroy this report when no longer needed. Do not return it to the originator.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| REPORT DOCUMENTATION PAGE | | READ INSTRUCTIONS BEFORE COMPLETING FORM |
|---|-----------------------|--|
| 1. REPORT NUMBER Technical Report No. 74-15 | 2. GOVT ACCESSION NO. | 3. RECIPIENT'S CATALOG NUMBER |
| 4. TITLE (and Subtitle) Locking Device For Vehicle Radios | | 5. TYPE OF REPORT & PERIOD COVERED Final Report |
| | | 6. PERFORMING ORG. REPORT NUMBER Technical Report No. 74-15 |
| 7. AUTHOR(s) Robert P. McGowan | | 8. CONTRACT OR GRANT NUMBER(s) |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Land Warfare Laboratory Aberdeen Proving Ground, MD 21005 | | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS LWL Task 06-M-72 |
| 11. CONTROLLING OFFICE NAME AND ADDRESS | | 12. REPORT DATE April 1974 |
| | | 13. NUMBER OF PAGES 16 Pgs |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) | | 15. SECURITY CLASS. (of this report) Unclassified |
| | | 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE |
| 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. | | |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) | | |
| 18. SUPPLEMENTARY NOTES TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL | | |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Radio Locking Device Locking Device for Radios Security Anti-Theft | | |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Army field units expressed a need to prevent unauthorized removal of radios from military tactical vehicles. A key locking device was developed for the AN/VRC-12 family of radios which replaces one of the wing-bolt clamps which attach the radio to the radio mount. The radio mount is secured to the vehicle with special security bolts. Evaluations were conducted by Army field units, and the device was found to be acceptable. | | |

DESCRIPTION

The Locking Device for Vehicle Radios is a key-operated lock for use with the AN/VRC-12 radio family to prevent unauthorized removal. It replaces one of the radio hold-down clamps which fasten the radio to the mount. See Figure 1. The locking device functions in the same way as the standard hold-down clamp, except a special allen-head bolt is used, and access to the bolt is obstructed by the locking cylinder. See Figure 2. In addition, the radio mount is fastened to the vehicle with special security bolts which are difficult to remove; the heads break-off when tightened, leaving only a rivet-type head. The key cannot be removed from the lock cylinder when unlocked. Each lock is furnished with the following (Figure 3):

| | |
|--|--------|
| Locking Device. | 1 ea. |
| Security Bolt, 5/16-18 x 1" Long | .5 ea. |
| Security Bolt, 5/16-18 x 1/2" Long | .5 ea. |
| Locknut, 5/16-18 | .5 ea. |
| Rollpin, 1/16" x 1/2" Long | .1 ea. |
| Bolt, Allen-Head, Special, 5/16-18. | .1 ea. |

The locks can be furnished in key-alike groups, or each key can be different. The locking cylinders may be removed, thereby deactivating the locks if desired. See Figure 2.

The Locking Device for Vehicle Radios is installed by first bolting the radio mount to the vehicle using the special security bolts supplied. The Locking Device is installed in place of the standard hold-down clamp and wing-bolt which are discarded. Based on a description of required characteristics, the device was developed by and procured from the Toepfer Lock Co., Milwaukee, Wisconsin.

EVALUATION

Seventy locking devices were sent to the 3d Armored Division in Europe. They were installed on VRC-46/VRC-49 (AN/VRC-12 family) radios mounted on M151 vehicles. The average installation time was 1/2-hour.

The evaluation period was 2 1/2 months. The locks fit and functioned as intended, and were considered an effective means to prevent unauthorized removal of the radios. See Appendix A. No incident of attempted unauthorized removal occurred during the evaluation period.

The removal of the security bolts which attach the radio mount to the vehicle was a maintenance problem. The security bolts can only be removed by drilling and use of an extractor.

DISCUSSION

No tests were made of the time required to defeat the lock. However, the lock is the same type used in telephone coin boxes, and has not often been defeated by picking. The keys are not easily duplicated without a special machine. Attempted removal of the locked clamp by force would deface the radio. Since the problem is primarily to maintain control of the radios and to prevent unauthorized diversion - rather than actual theft - it is believed that the degree of security afforded by the device is adequate.

No acceptably simple method is evident for overcoming the maintenance problem of removing the security bolts. Once the radio is removed, removal of the bolts with the proper tools can be accomplished in 1/2 hour or less.

CONCLUSION

The Locking Device for Vehicle Radios provides an acceptable means to prevent unauthorized removal of AN/VRC-12 family radios from military vehicles.




FIGURE NO. 2: Removing (or Installing) Locking Cylinder




FIGURE NO. 3: Radio Locking Device Components

APPENDIX A
RADIO LOCKING DEVICE
INSTALLATION QUESTIONNAIRE

1. Dates of Installation: Week of January 2, 1974
2. Location and Unit Designation: Hanau, FRG, 3d Armored Division Artillery
3. Review the parts list. Were the locks and installation hardware received complete? Yes. List missing items: None
4. Models of vehicles on which installed. List: M151
5. Was the installation hardware furnished adequate for each vehicle? Yes. If not explain in detail _____
6. Models of radios on which locks were installed: VRC-46, VRC-49
7. Was there any misfit with any radio? No. If so, explain in detail: _____
8. Did the locks function properly? Yes. If not, explain in detail: _____
9. What was the average installation time - manhours? $\frac{1}{2}$ hour

William Evans
WILLIAM EVANS, CPT
DivArty Signal Officer

RADIO LOCKING DEVICE

FINAL EVALUATION QUESTIONNAIRE

1. Do you think that the Radio Locking Device is an effective means of preventing theft or unauthorized removal of radios? Yes
2. Do you think all vehicle radio installations should use the lock? Yes
What is your recommended BOI? One per AN/VRC-12 Family of radio sets
3. What improvements to the device do you suggest? See #6
4. What form of key plan do you suggest? That is, should all keys within a unit be the same, or all different? Sets of identical keys per section
5. Is the "key retained when unlocked" a desired feature? Yes
6. Add any additional comments you wish to make: The headless bolts present a maintenance problem. When a vehicle is turned in for maintenance the radio mount is removed. If the headless bolts are used it requires drilling and using an extractor to get the mount off.



CURLEY B. KNEPP, CPT
Division Radio Officer

FORMAT FOR USER OPERATIONAL EVALUATION STATEMENT

The Radio Locking Device has been in use by Army elements in West Germany since January 1974.

Analysis of performance since that time indicates that:

1. The Radio Locking Device (is/~~is not~~) safe in operation.
2. Its reliability (is/~~is not~~) acceptable to this Command.
3. Its maintainability (is/~~is not~~) acceptable to this Command.
4. It requires (~~only normal~~/special) support provisions. Requires drilling and extraction to remove mount for maintenance.
5. Technical risk connected with the continued fielding of this item is (low/~~moderate~~/high).
6. The Radio Locking Device (is/~~is not~~) acceptable to this Command for operational use. It (~~satisfies~~/does not satisfy)* all requirements of this Command. Based upon its performance in this operational environment, this item (should/~~should not~~) be considered for adoption Army-wide. Recommend type classification as Standard B.


JOHN A. HOEFLING
Brigadier General, USA
Assistant Division Commander

* Security of AN/VRC 12 family of radio sets only.

DISTRIBUTION LIST

| | <u>Copies</u> |
|--|---------------|
| Commander US Army Materiel Command ATTN: AMCDL 5001 Eisenhower Avenue Alexandria, VA 22333 | 1 |
| Commander US Army Materiel Command ATTN: AMCRD 5001 Eisenhower Avenue Alexandria, VA 22333 | 3 |
| Commander US Army Materiel Command ATTN: AMCRD-P 5001 Eisenhower Avenue Alexandria, VA 22333 | 1 |
| Director of Defense, Research & Engineering Department of Defense WASH DC 20301 | 1 |
| Director Defense Advanced Research Projects Agency WASH DC 20301 | 3 |
| HQDA (DARD-DDC) WASH DC 20310 | 4 |
| HQDA (DARD-ARZ-C) WASH DC 20310 | 1 |
| HQDA (DAFD-ZB) WASH DC 20310 | 1 |
| HQDA (DAMO-PLW) WASH DC 20310 | 1 |
| Commander US Army Training & Doctrine Command ATTN: ATCD Fort Monroe, VA 23651 | 1 |

| | |
|--|---|
| Commander US Army Combined Arms Combat Developments Activity (PROV) Fort Leavenworth, KS 66027 | 1 |
| Commander US Army Logistics Center Fort Lee, VA 23801 | 1 |
| Commander US Army CDC Intelligence & Control Systems Group Fort Belvoir, VA 22060 | 1 |
| TRADOC Liaison Office HQS USATECOM Aberdeen Proving Ground, MD 21005 | 1 |
| Commander US Army Test and Evaluation Command Aberdeen Proving Ground, MD 21005 | 1 |
| Commander US Army John F. Kennedy Center for Military Assistance Fort Bragg, NC 28307 | 1 |
| Commander-In-Chief US Army Pacific ATTN: GPOP-FD APO San Francisco 96558 | 1 |
| Commander Eighth US Army ATTN: EAGO-P APO San Francisco 96301 | 1 |
| Commander Eighth US Army ATTN: EAGO-FD APO San Francisco 96301 | 1 |
| Commander-In-Chief US Army Europe ATTN: AEAGC-ND APO New York 09403 | 4 |
| Commander US Army Alaska ATTN: ARACD APO Seattle 98749 | 1 |

| | |
|---|----|
| Commander MASSTER ATTN: Combat Service Support & Special Programs Directorate Fort Hood, TX 76544 | 1 |
| Commander US MAC-T & JUSMAG-T ATTN: MACTRD APO San Francisco 96346 | 2 |
| Senior Standardization Representative US Army Standardization Group, Australia c/o American Embassy APO San Francisco 96404 | 1 |
| Senior Standardization Representative US Army Standardization Group, UK Box 65 FPO New York 09510 | 1 |
| Senior Standardization Representative US Army Standardization Group, Canada Canadian Forces Headquarters Ottawa, Canada K1A0K2 | 1 |
| Director Air University Library ATTN: AUL3T-64-572 Maxwell Air Force Base, AL 36112 | 1 |
| Battelle Memorial Institute Tactical Technical Center Columbus Laboratories 505 King Avenue Columbus, OH 43201 | 1 |
| Defense Documentation Center (ASTIA) Cameron Station Alexandria, VA 22314 | 12 |
| Commander Aberdeen Proving Ground ATTN: STEAP-TL Aberdeen Proving Ground, MD 21005 | 2 |
| Commander US Army Edgewood Arsenal ATTN: SMUEA-TS-L Aberdeen Proving Ground, MD 21010 | 1 |

| | |
|---|---|
| US Marine Corps Liaison Officer Aberdeen Proving Ground, MD 21005 | 1 |
| Director Night Vision Laboratory US Army Electronics Command ATTN: AMSEL-IV-D (Mr. Goldberg) Fort Belvoir, VA 22060 | 1 |
| Commander US Air Force Special Communications Center (USAFSS) ATTN: SUR San Antonio, TX 78243 | 1 |
| Commander US Army Armament Command ATTN: AMSAR-ASF Rock Island, IL 61201 | 1 |
| Commander US Army Tank Automotive Command ATTN: AMSTA-RKMD Warren, MI 48090 | 2 |
| Commander US Army Electronics Command ATTN: AMSEL-CR Fort Monmouth, NJ 07703 | 2 |